

Monimax™ 5600

Value, Delivered

Interior Freestanding Cash Dispenser

Would you like an ATM that you can count on?

Features

- **Maximum Reliability** - Monimax 5600 is designed to provide 2nd to none reliability in the market with highest uptime and with minimum maintenance needs. You won't have to worry about replacing the parts or sudden breakdowns because the Monimax 5600 is designed to run for a very long time, problem-free.
- **Environment Stewardship** - With quality comes also responsibility. Monimax series are equipped with energy saving features like low energy LCD and long lasting ATM parts with minimum implications to the environment.
- **Flexibility** - Monimax series are designed with open architecture platform allowing for easy future upgrades and module modifications. Modular design is one of ways in which we are trying to save our customers' cost and provide maximum convenience.
- **Ultimate Functionality** - Monimax 5600 offers ultimate functionality featuring bill payment, funds transfer, mobile top-up in a highly user friendly interface for maximum convenience and very easy transition.
- **Maximum Protection** - Complying to standards in various regions worldwide, Nautilus Hyosung offers advanced security measures while highly secured integrity of the Monimax 5600 prevents any attempted security breaches from occurring. Monimax 5600 is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



Driving tomorrow's technology
NAUTILUS HYOSUNG

Dependable Customer Service:

We understand the importance of speedy resolution to any issues arising in the operation. Our representatives offer real solutions with real results for maximum return on your investment.



System Platform

- Microsoft® Window® XP platform
- NDC+, DDC912, User application

Communication

- TCP/ IP, Wireless, X.25, Dial-up

Display

- 15" color TFT LCD
- Privacy filter
- Sunlight readable

Input Type

- 8 function keys
- Touch screen
- PCI compliant EPP
T-DES, DES, RSA

Security

- UL 291 Level 1 safe
- Mechanical combination lock
- Electronic lock
- KABA Mas cencon lock
- 1st security camera
- 2nd security camera
- Fingerprint reader

Card reader

- Dip hybrid card reader
- Motorized hybrid card reader
- Contactless card reader
- EMV level 1,2 compliant
- Anti-skimming device

Cash dispenser

- 3,000 notes cassette
- Up to 4 cassettes
- Bundle present
- Bundle retraction
- Note by note rejection
- Automatic shutter

Printers

- Graphical thermal receipt printer
- Journal printer (Thermal, Dot)

Additional Features

- VFD (Vacuum fluorescent display)
- Lead-through indicator
- 1D/2D Barcode reader
- Heater
- Audio jack
- Speaker

Power Supply

- AC 110 ~ 240V, 50 ~ 60 Hz
- Backup battery
(Reserving last transaction & safe shutdown)

Environmental Conditions

- Temperature
0°C ~ 40°C (32°F ~ 104°F)
-31°C ~ 40°C (-24°F ~ 104°F) with heater
- Humidity
20% ~ 85%

Dimensions

- Height : 1,505mm (59.3")
- Width : 463mm (18.2")
- Depth : 811mm (31.9")

All dimensions are cabinet & safe size

- Weight : 444kg (978 lbs)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.