

Easy, Fast & Secure Card Issuance Machine MoniValue 400 Operational Efficiency & Better Customer Experience.

*MV400 is, as an intelligent and powerful card issuing kiosk,
to deliver fast, secure and personalized card issuing service.
MV400 offers proven reliability, easy operation and less maintenance.*

Improved productivity in branch

The reliable & powerful MoniValue400 enables to maximize branch productivity by shortening the customer queue for card issuance & reducing issuance costs.

Minimum Maintenance Needs

Greater serviceability in system configuration makes diagnosis and repair easy; and high reliability lowers maintenance needs and costs.

Higher Customer Satisfaction

Versatile printing (e.g. monochrome or full colored, dual-side) satisfies diverse customer preference. It personalizes customer service with the edge-to-edge card issuance.



System Platform

- Microsoft Windows 10
- Hyosung Moniplus™ XFS

Customer Interface

- 21.5 inch display
- Lead-through Indicator
- PIN Pad – PCI compliant
- Card Reader – EMV Ready (Dip, Motorized)
- Contactless card reader (Integrated NFC reader via card, smartphone or smartwatch)
- Audio – speaker / earphone jack

Printer

- Receipt printer : graphical thermal printer
- Journal printer : e-Journal (Thermal printer optional)

Media Technology

- Card Dispenser
 - Motorized card issuance
 - Color / Mono Print
 - Dual-side print (optional)
 - EMV compliant, RF Read / Write
 - 8 Hoppers x 100ea (70ea Embossed)

Cash Acceptor (optional)

- 600 / 1,200 notes capacity cashbox
- Single Acceptor

Security

- Safe : UL291 Level 1
- Lock : Electronic lock, Mechanical combination lock
- Sensor : Alarm (Heat & Seismic), Door sensor
- Privacy filter
- Anti skimming, Anti card trapping, Anti shimming, Anti cash trapping
- Security camera (Face & Hand)
- MoniGuard endpoint security software

Additional Features

- Barcode reader
- Fingerprint reader
- Document scanner
- Document printer
- ID scanner
- Sign Pad

Power Supply

- AC 110 ~ 240V, 50 ~ 60Hz
- Backup battery

Environmental Conditions

- Temperature : 0°C ~ 40°C (32°F ~ 104°F)
- Humidity : 25% ~ 85%

Dimensions

- Height : 1,416mm (55.8 inch)
- Width : 625mm (24.6 inch)
- Depth : 798.3mm (31.4 inch)
- Weight : 300kg (661.39 lbs.)

※ Internal Components may change with introduction of new technology. Hyosung TNS reserves the right to change the specifications of this ATM to accommodate the changes in technology.

