



# T300 Unattended Payment Terminal



## Perfectly fit for self-service solutions

SPECTRA's T300 unattended payment terminal offers a robust set of payment features, is operationally reliable in totally unattended environments, and comes housed in a durable, long-lasting case.

It is one of just a few payment terminals in the market that meets all of the prerequisites to be endorsed as a truly "unattended" unit. It is also certified for use in the outdoor environments, in both heat and cold, and is water and dust resistant. Like all of SPECTRA's devices, it is built to perform as expected... and last.

To ensure customer satisfaction, we work with you to integrate it into your unique retail environment. This sturdy little device pairs perfectly with kiosks, ticketing centers, gasoline pumps, and vending machines. Our goal: to increase transaction efficiency and deliver a hassle-free customer experience.



# Features of T300 Unattended Payment Terminal

- Support Magnetic, IC card and NFC card
- Generate dynamic QR code
- High performance ARM® Cortex secure processor
- Large TFT LCD color display
- Build in MDB interface connect with vending machine controller
- IP54 protection from dust ingress and wet working environment (valid for NFC terminal only)
- Support Ethernet, 3G WCDMA & Bluetooth®
- USB OTG interface
- PCI 5.X

## Optional

- Touch screen
- Camera
- WIFI
- Ethernet

## Specifications

Payment acceptance types	Magnetic track 1/2/3 IC card NFC
Processor	ARM® Cortex secure processor
Memory	64MB RAM, 128/512MB Flash
Display	2.8" TFT LCD color display (320 x 240) Touch screen (optional)
Keys	15 keys No keypad (optional)
Card slots	SAM x 1 & SIM x 2 OR SAM x 2 & SIM x 1
Communication interface	Ethernet, 3G WCDMA, Bluetooth®
Peripheral	RS232 Port @ 115200 bps (RJ11 port) MDB slave x 1 OTG USB x 1
Audio	Optional
Power supply	DC 9V with DC power socket, MDB power
Certifications	PCI v5.x (PTS, OP, SRED)    EMV/PBOC L1 & L2 Visa PayWave                    MasterCard Contactless MasterCard TQM                American Express ExpressPay CUP QuickPass                JCB J/Speedy FCC/CE
IP no.	IP54 (no ICC and Magstripe)
Operating temperature	-20 - 65 °C
Storage temperature	-20 - 65 °C
Operating humidity	5-90% non-condense
Dimensions & weight	165 (L) x 80 (W) x 57 (H) mm 340g

\*Specifications is subject to change without prior notice.

## Fit for any unattended scenarios!

